ROTARY
BY ROTARY SOLUTIONS

SYMMETRIC 2-POST LIFT SERIES
12,000 lbs. CAPACITY

SP012-AV

WIDER DRIVE-THRU AND LARGER FOOTPRINT FOR SHOPS WORKING ON TALLER, HEAVIER VEHICLES

Wide design provides the drive-thru clearance for greater under vehicle access and less obstruction for service to battery electric vehicles.

INCLUDES LOW-PROFILE ALL VEHICLE AV ARMS® FOR ADDED REACH

SIMPLY LIFT ANYTHING!★

CHOOSE YOUR:
- Lift height and width
- Power option
- Productivity accessories

FEATURES:
- Rise height of over 75"
- Original "Double S" column design
- ALI Gold Certified

Standard with adjustable TA truck and RA round poly adapters for use on framed and unibody vehicles.

Includes (4 each) 3 1/2" and 5" adapter extensions plus storage rack.



Model shown: **SP012N20M5BL**

OPTIONAL LIFT CONFIGURATIONS

5 HEIGHT OPTIONS
Add up to 3' of additional height
STANDARD HEIGHT: 13' 8"
+1' to 14' 8" / +2' to 15' 8" / +3' to 16' 8"
LOW-CEILING HEIGHT: 11' 8"

3 STANDARD WIDTH OPTIONS
Add up to 12" of additional drive-thru for wider vehicles

OPTIONAL WIDE OVERHEAD KIT #FJ71037
Enables a 17" wider 12' 10-5/8" column stance. 8-1/2" lower lift overhead setting is used with this kit.
Contact factory for details.

AVAILABLE WITH SHOCKWAVE™ EQUIPPED DC POWER
Battery powered SHOCKWAVE™ lifts with onboard 110v charger provide *2X the lifting speed of standard lifts!*

SHOCKWAVE EQUIPPED

SCAN TO WATCH PRODUCT VIDEO

SPECIFICATIONS SP012-AV BL = Blue / RD = Red	STANDARD HEIGHT SP012N20M5BL/RD LOW CEILING HEIGHT SP012N20MLBL/RD	
Rise*	75 3/4" - 78 1/8"	
Overall Height	13' 8" STANDARD	11' 8" LOW
Overall Width	11' 5 5/8" to 12' 5 5/8"	
Drive-thru	102 3/8" to 114 3/8"	
Inside Columns	114 7/8" to 126 7/8"	
Arm Reach Min/Max	27 1/2" / 59"	
Min. Adapter Height**	3 7/8"	
Min. Bay Size	12' x 26'	
Min. Ceiling Height	13' 9" STANDARD	11' 10 3/4" LOW
Motor / Voltage 1Ø	2 HP, 208-230V **5 HP - 110V with SHOCKWAVE**	
Time of Full Rise	60 seconds **25 seconds with SHOCKWAVE*****	

Heights and widths reflect standard settings.
* Rise measures lowest and highest position of the supplied adapters from floor to full cylinder stroke.
** Min. adapter height measured with arm at full extension.
***Actual rise and descent times vary depending on vehicle weight.

★ WITHIN LIFT'S RATED CAPACITY AND VEHICLE CLEARANCE.

Rotary® PART OF VSG a DOVER company
ROTARY SOLUTIONS

To learn more about all of our automotive service and repair solutions or to contact your local distributor, visit us at **www.RotarySolutions.com** today.

Need assistance or have questions? We're here to help: 800.445.5438
Sales: insidesales@rotarysolutions.com / Technical Support: HD-techsupport@rotarysolutions.com

ROTARY SOLUTIONS™
2700 Lanier Drive | Madison, IN 47250, U.S.A.
Lit# **Rotary.SP012AV.Cutsheet.11.01.2026**

©2026 VEHICLE SERVICE GROUP™
All Rights Reserved. Unless otherwise indicated, ROTARY SOLUTIONS™, VEHICLE SERVICE GROUP™, DOVER® and all other trademarks are property of Dover Corporation and its affiliates.
Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.